

Chirality in multilayers probed by Soft x-ray (coherent) scattering

N. Jaouen^{1*}, C. Leveillé¹, E. Burgos Parra^{1,2}, Y. Sassi², W. Legrand², F. Ajejas², V. Cros²,
N. Reyren²

1. Synchrotron SOLEIL, Saint-Aubin, 91192 Gif-sur-Yvette Cedex, France

*2. Unité Mixte de Physique, CNRS, Thales, Univ. Paris-Sud, Université Paris-Saclay, 91192
Palaiseau, France*

Many current forthcoming applications of magnetic materials involve heterostructures or alloys containing magnetic and non-magnetic elements. X-ray Resonant (Coherent) Scattering is the technique of choice to probe such phenomena thanks to its element-selectivity and spatial sensitivity.

In this presentation I will introduce the experimental set-up that we developed at SOLEIL and illustrate their capabilities. SEXTANTS [1] is a beamline of the SOLEIL synchrotron, covering the 50-1700eV energy range dedicated to soft x-ray scattering. The resolving power exceeds 10000 and maximum flux on the sample ranges from 1×10^{14} (100 eV) to 2×10^{13} (1000 eV) ph./s/0.1% bw. The beamline main objective is the investigation of the electronic and magnetic properties of solids using three scattering techniques: resonant inelastic x-ray scattering (RIXS), x-ray resonant magnetic scattering (XRMS) and coherent x-ray scattering (CXS), the last one including also imaging via Fourier transform holography (FTH) [2, 3].

In the second part, several recent results obtained at SEXTANTS beamline will be presented, and in particular I will show that XRMS is the tool to study magnetic chirality in prototype Pt/Co multilayers in which Dzyaloshinskii-Morya interaction (DMI) is induced by the inversion symmetry breaking at the interfaces [3] and how it was possible to reveal the hybrid character of the magnetic structure in thick multilayer [4]. I will also present how one can manipulate this magnetic chirality either statically using magnetic field or at the femtosecond timescale using optical light.

In the last part I will present the latest development of resonant scattering and in particular how the use of the x-ray coherence already available at modern light source, and expected to increase by few order of magnitude in the planned upgrade sources, allow nowadays to image the sample with a spatial resolution of few tens of nanometers and a time resolution ranging from ns down to few ps timescale.

[1] M. Sacchi et al., Journal of Physics: Conference Series **425** (2013) 072018

[2] S. Eisebitt et al., Nature, 432, 885 (2004).

[3] H. Popescu et al., J. Synchr. Rad 26(1), 280-290 (2019)

[3] J.Y. Chauleau et al., Phys. Rev. Lett. 120, 037202 (2018).

[4] W. Legrand et al, Sci. Adv. 2018; 4:eaat0415 (2018).

*Corresponding author: nicolas.jaouen@synchrotron-soleil.fr